

PROVEN PERFORMER

On-Premises Tumble Dryers

SA120, SA170, SA200

Features


- · Large cylinder
 - allows free air movement
 - short drying cycles
- · Large door opening for easy loading and unloading
 - extra strong hinge
- Standard galvanized drum
 - oval drum holes preventing damage from standard drywall screws (not SA200)
- Unique drum supporting system
 - at the rear: bearing house
- · Large lint filter
 - easy removal of lint
 - efficient drying
- · Radial airflow
 - drum perforations over the entire surface
 - high production
 - pulley drive system
- Reversing standard: prevents tangling of the linen
- High performance heating
- Quantum[™] Gold Control
 - easy to operate, easy to program
 - flexibility of 30 programmable cycles
 - moisture sensing technology prevents overdrying, saving time and energy
- · Digital display and countdown
- C.A.R.E. (Combustion Auto Response Equipped)
 - A response to laundry combustion
 - monitoring the temperature in the drum
 - in case of excessive temperature, linen is sprayed with water



- revolutionary rotary transfer switch enables the system to sense dryness levels thousands of times per second for ultra-acurate readings
- sensing surface models offer up to 267 times more surface area for sensing than competitors
- industry exclusive rotary transfer switch doesn't require brushes or hard contact, giving maintenancefree, reliable performance
- dryer stops automatically when desired dryness level is reached, preventing staff from making educated
- step-dry enables the use of heat until the load is half dry, then lowering the temperature for the remainder of the cycle until the specified dryness level is reached
- dryness level settings ranging from 0 to 40 percent allows you to deine each cycle according to your specifc needs

Options

- · Stainless steel front and drum
- · Steam heat
- Electric Heat (SA120 only)



Quantum™ Gold Control





	SA120	SA170	SA200		
Drum					
Capacity 20:1 kg	54.4	77.1	90.7		
Volume I	1021	1408	1656		
Cylinder diameter mm	1118	1289	1289		
Motor	1110	1209	1209		
Fan kW (non-rev/rev)	0.75	2.24	2.24		
Orive kW (non-rev/rev)	0.56	0.56	0.56		
Programmer	0.50	0.50	0.90		
ype of control	Quantum Gold	Ouantum Gold	Ouantum Gold		
Cabinet	Qualituiii Gold	Quantum Gold	Quantum Cold		
Colour	White, option stainless steel	White, option stainless steel	White, option stainless steel		
Drum	Galvanized, option stainless steel	Galvanized, option stainless steel	* 1		
	1 1	7 1	Galvanized, option stainless steel		
Oryer door handle	Black plastic	Black plastic	Black plastic		
leating		2.11/	0.110		
Gas	285 MJ/hr	416 MJ/hr	446 MJ/hr		
Electric	60kW	n/a	n/a		
Steam @ 100psi (6.9 bar)	11.7 BHP (118.5 kW)	18.8 BHP (189.7 kW)	18.8 BHP (189.7 kW)		
Steam @ 15 psi (1.0 bar)	7.9 BHP (79.7 kW)	12.6 BHP (126.9 kW)	12.6 BHP (126.9 kW)		
Connection					
Gas and Steam	Rev Amps	Rev Amps	Rev Amps		
115/50/3 3W+G	3.8	6.9	8.0		
Make up air supply	2323 cm²	3387 cm²	3387 cm ²		
Air outlet diameter mm	254	305	305		
Steam inlet (NPT)	19mm	19mm	19mm		
Steam Outlet (NPT)	19mm	25mm	25mm		
Gas inlet (NPT)	25mm	25mm	25mm		
Operation					
Decibel Rating	66 dBA	66 dBA	66 dBA		
Orying cycles	30	30	30		
Power					
With reversing (where available)	Standard	Standard	Standard		
Motor horsepower Fan kW (non-rev/rev)	0.75	2.24	2.24		
Motor horsepower Drive kW (non-rev/rev)	0.56	0.56	0.56		
Transport data					
Gross weight kg	607	756	825		
Net weight kg	578 (steam 624)	714 (steam 760)	790 (steam 820)		
Dimensions H×W×D mm	2177×1178×1725	2388x1349x1749	2388×1349×1939		
Packaging dimension H×W×D mm	2286×1232×1829	2515×1473×1892	2515×1413×2019		
Volume m³	5.2	7.0	7.2		
Agency approvals	5.2	,	7.2		
Australian gas approval	# 5646	# 5646	# 5646		
CE approval	Yes	Yes	Yes		






























	A	В	С	D	Е	F	G	н
SA120	797	826	1242	1268	1725	1153	1178	2177
SA170	860	826	1289	1314	1749	1324	1349	2388
SA200	815	904	1473	1505	1939	1324	1349	2388
					depth		width	height

All measurements are in mm.

































Speed Queen Equipment Sales. 26 Theobald Street, Thornbury, Vic 3071 Ph: (03) 9495 1300 Fax: (03) 9495 1600

www.speedqueensales.com.au W: E: sales@speedqueensales.com.au Servicing Victoria, Tasmania.